

Technical Data Sheet (TDS)

OCTANE BOOSTER Kim B4

ITEM	UNIT	RESULT
FLASH POINT	°C	<28
DENSITY	kg/m3	870
APPEARANCE	-	Clear and free of impurities
COLOR	-	<0.5
KIN. VISCOSITY	°C	
POUR POINT	°C	
COPPER CORROSION	°C	1a
SULFUR	ppm	199
DISTILLATION (IBP)	°C	120
DISTILLATION (5%)	°C	
DISTILLATION (10%)	°C	131
DISTILLATION (20%)	°C	132
DISTILLATION (30%)	°C	132
DISTILLATION (40%)	°C	133
DISTILLATION (50%)	°C	134
DISTILLATION (60%)	°C	134
DISTILLATION (70%)	°C	135
DISTILLATION (80%)	°C	135
DISTILLATION (90%)	°C	135
DISTILLATION (95%)	°C	136
DISTILLATION (FBP)	°C	145
RECOVERD (DENSTY @200°C)	%VOL	
RECOVERD (DENSTY @357°C)	%VOL	
DISTILLATION (RECOVERY)	%VOL	99
DISTILLATION (RESIDUE)	%VOL	0.1
DISTILLATION (LOSS)	%VOL	0.9



Phone: +9821 910 204 06
Fax: +9821 66 28 96 38



Email: info@keaholding.co
Web: www.keaholding.co



Unit c, Level 4, No.1, Moallem Blvd,
Saeidi Highway, Tehran, Iran.