

Technical Data Sheet (TDS)

OCTANE BOOSTER Kim B3

ITEM	UNIT	RESULT
FLASH POINT	°C	<28
DENSITY	kg/m ³	865
APPEARANCE	-	Transparent
COLOR	-	<0.5
KIN. VISCOSITY	°C	0.75
POUR POINT	°C	<-45
COPPER CORROSION	°C	1a
SULFUR	ppm	279
DISTILLATION (IBP)	°C	58
DISTILLATION (5%)	°C	64
DISTILLATION (10%)	°C	68
DISTILLATION (20%)	°C	78.5
DISTILLATION (30%)	°C	92.5
DISTILLATION (40%)	°C	112
DISTILLATION (50%)	°C	130
DISTILLATION (60%)	°C	135
DISTILLATION (70%)	°C	137
DISTILLATION (80%)	°C	137
DISTILLATION (90%)	°C	137
DISTILLATION (95%)	°C	137
DISTILLATION (FBP)	°C	149
RECOVERD (DENSTY @200°C)	%VOL	
RECOVERD (DENSTY @357°C)	%VOL	
DISTILLATION (RECOVERY)	%VOL	99
DISTILLATION (RESIDUE)	%VOL	0.1
DISTILLATION (LOSS)	%VOL	0.9

